


Ikon

IKL60 Louvre



Product description

58.7 x 10mm elliptical straight sided extruded aluminium blades

Fixed solar shading/privacy/security screen

Sliding solar shading/privacy screen using propriety rollers, guides and track. Can be top hung or bottom rolling.

Side hinged with butt hinges and keyed lock. Top hung with telescopic gas struts

All projects are assessed individually

Pitch 60mm—can be varied project specific

Blade angle 45 degrees—can be varied project specific.

Maximum free area varies depending on blade angle and pitch

Standard RAL or BS colours. Anodizing to special order.

Product testing

Impact resistance to BS EN 13049:2003 achieving Class 5 Wintech Test report R14340-2

Wind resistance to BS EN12211:2000 and BS EN 12210:2000 achieving Class 4

Tested project specific to 2210 pascals. Wintech Test report R14340-3

Impact resistance sample 1000 x 2500, 60mm pitch 45 degree angle

Wind resistance sample 1200 x 2850, 60mm pitch 45 degree angle

Unit 1 Yardley Brook Industrial Park, Leaford Way, Shard End, Birmingham, B33 9TX

Tel: 0121 789 9936, Fax 0121 783 7905, Web : www.ikonaluminium.com, Sales : info@ikonaluminium.co.uk